

# TOPAZ - ACC

Model Reference	Luminaire Power (tcW)	Engine Output (lm)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	Colour Temperature (K)	Colour Rendering (Ra)	Nominal Weight (Kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection (Front)	Ingress Protection (Rear)	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Life L90/F10 (Khours)	Light Source Energy Class
ACC001	8.0	625	474	59.9	2700	90	0.3	220 - 240	50 - 60	IP44	IP20	3	-25°C	+35°C	5	>55	E
ACC002	6.5	650	499	77.9	3000	80								+35°C	5	>55	D
ACC003	6.5	700	531	82.9	4000	80								+35°C	5	>55	C
ACC004	10.0	850	646	65.4	2700	90								+25°C	5	>55	E
ACC005	7.5	850	659	85.6	3000	80								+25°C	5	>55	D
ACC006	7.5	900	700	90.9	4000	80								+25°C	5	>55	C
ACC007	13.5	1150	880	65.6	2700	90								+25°C	5	>55	E
ACC008	11.5	1250	964	84.4	3000	80								+25°C	5	>55	D
ACC009	11.5	1325	1021	89.5	4000	80								+25°C	5	>55	C

**Please note:** Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-288T-REV5 28/10/2024



Thornhill Road Business Park  
Tenter Fields, Dewsbury  
West Yorkshire  
WF12 9QT  
+44 [0]1924 482777  
www.gamma-uk.com

