

VORTEX ADI

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Light Source Power (W)	Light Source Output (lm)	Light Source Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (llm)	Luminaire Efficacy (llm/tcW)	UGR	BLF (EM ONLY)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)
ADI001	830	80	5.5	822	151	7.5	700	93	22.5	0.35	0.4	220-240	50-60	IP65	IP44	3	-20
ADI002	840	80	5.5	860	158	7.5	725	104	22.4	0.35							
ADI003	830	80	7.5	1037	138	9.0	875	97	23.3	0.28							
ADI004	840	80	7.5	1085	145	9.0	925	103	23.2	0.28							

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification.

GDS-310T-REV3 22/05/2025



Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

