

Eco designed	Long life	Low glare Options
Renewable luminaire	Warranty 5 years	Emergency Options
98% Recyclable	Length Options	Dimming Options

### KEY FEATURES

- Recessed, extruded continuous linear profile luminaire
- Through-wiring in all lengths
- Tridonic low energy LED and driver system
- TP(a) opal lens for feature, general and visual areas
- Low glare prismatic lens available for office and LG7 compliance
- Life up to >72,000 hours L80/F10
- Efficacy up to 140 lm/tcW
- Finished in RAL 9016 white
- Available in 3 standard 'building block' lengths

### DIMENSIONS

**Cut-outs**

850	=	842 x 58 mm
1.2	=	1261 x 58 mm
1.5	=	1540 x 58 mm

Add 6 mm at both ends to allow for end caps


### ORDERING INFORMATION

Length (m)	Colour	Luminaire output (lm)	Model ref.	Luminaire output /LO (lm)	Luminaire output /HO (lm)
0.85	830	1725	AHC001	1175	2725
0.85	840	1800	AHC002	1225	2850
1.2	830	2550	AHC003	1725	4075
1.2	840	2700	AHC004	1825	4275
1.5	830	3125	AHC005	2125	5000
1.5	840	3300	AHC006	2250	5225

### OPTIONS

Options	Suffix
Low / high output	/LO, /HO
Control gear	/ECO
Emergency - Integral indicator*	/EMI, /EMDI, /EMSI
Low glare prismatic diffuser	/LG
Pair of end caps	SECAP
Joining / through-wiring kit	JKIT
Diffuser removal tool	PT001


\* Emergency options not available with AHC001 or AHC002



**/LO**  
Lower output



**/HO**  
Higher output




**/ECO**  
SwitchDIM, DALI or DSI  
control gear



**/EMI**  
Emergency  
Integral indicator \*



**/EMDI**  
DALI emergency  
Integral indicator \*



**/EMSI**  
Self-test emergency  
Integral indicator \*



**/LG**  
Low glare prismatic  
diffuser



**SECAP**  
Pair of endcaps



**JKIT**  
Joining / through-wiring  
kit



**PT001**  
Diffuser removal tool

\* Emergency options not available with AHC001 or AHC002