To accompany Note AGB Datasheet GDS-398

NOTE - AGB

Model Reference	Colour Temperature (K)	Colour Rendering (Ra)	Light Source Power (W)	Light Source Output (lm)	Light Source Efficacy (lm/W)	Luminaire Power (tcW)	Luminaire Output (Llm)	Luminaire Efficacy (Llm/tcW)	UGR	BLF (EM ONLY)	Nominal Weight (kg)	Mains Voltage (V)	Mains Frequency (Hz)	Ingress Protection - Front	Ingress Protection - Rear	MacAdam (SDCM)	Minimum Operating Temperature (°C)	Maximum Operating Temperature (°C)	Warranty (Years)	Power Factor	Life L70/B50 (Khours)	Light Source Energy Class
AGB001	2700	90	9.5	800	84	9.5	700	74	16.8	N/A	0.25	220-240	50-60	IP54	IP20	3.0	-25°	35.0	5	>0.9	>54k h	F
AGB002	3000		9.5	850	89	9.5	725	76	17	N/A												F
AGB003	4000		9.5	875	92	9.5	750	79	17.3	N/A												F
AGB004	2700		8.0	975	122	10.0	850	85	17.6	28%											>54k h	F
AGB005	3000		8.0	1075	134	10.0	925	93	18.2	28%												F
AGB006	4000		8.0	1150	144	10.0	975	98	18.3	28%												F
AGB007	2700		12.0	1300	108	14.0	1125	80	18.9	19%											>54k h	F
AGB008	3000		12.0	1425	119	14.0	1225	88	19.2	19%												F
AGB009	4000		12.0	1450	121	14.0	1250	89	19.1	19%												F

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes.
Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification. E&OE.

GDS-398T-REV3 16/092026

GAMMA ILLUMINATION
Thornhill Road Business Park
Tenter Fields, Dewsbury
West Yorkshire
WF12 9QT
+44 (0)1924 482777
www.gamma-uk.com

Society of Light and Lighting Sustaining Member 2024
ICEL
WEEE Scheme RecoLight MEMBER
MADE IN BRITAIN Membership 1835
bsi ISO 9001 Quality Management Systems CERTIFIED FS 593079
LIAQA ASSURED COMPANY